

Brava Old World Slate









Beautifully authentic high-performance roofing.

The beautiful look of a slate roof without the maintenance.

Truly realistic

Our proprietary process creates the most authentic-looking old world slate on the market.

Superior performance

Brava is designed to withstand even the most severe weather, boasting the highest hail resistance rating in the industry.

Enhanced curb appeal

Curb appeal directly correlates with owner satisfaction and higher property value.

Maintenance free

Brava's proprietary formulation ensures extreme durability.

Color technology

Brava's proprietary multi-coloring process means you get the authentic appearance of a natural product, complete with variegated colors throughout the entire product.

Fully sustainable

Brava uses recycled material to create a roof that is fully recyclable.

Complete

Brava offers a complete line of accessory tiles.

Unparalleled Performance

























Tuscan Clay

Note: Premium Blend and Title 24 Cool Roof Colors are available as an upcharge from Standard Color pricing. Please consult your sales representative for additional information.

| Description | Weight | Dimensions |
|--|------------------------------|--|
| 6" Field Tile | 1.4 lbs. | 6" x 22" |
| 9" Field Tile | 1.8 lbs. | 9" x 22" |
| 12" Field Tile | 2.7 lbs. | 12" x 22" |
| Starter | 1.6 lbs. | 12" x 12" |
| Hip & Ridge | 2.0 lbs. | 5 ⁵ / ₈ " x 6" x 16" |
| Solid Multi-Width Accessory | 4.5 lbs. | 12" x 22 ⁷ / ₈ " |
| Weight Per Square (standard slate) Weight Per Square (Multi-Width Slate) | 311 lbs./sq. 305 lbs./sq. | |

| Aesthetics | Brava Old World Slate | Natural Slate |
|--|--------------------------|-------------------------|
| Authentic Look | √ | \checkmark |
| 1" Thickness | \checkmark | × |
| Multi-Colored Variegated | \checkmark | Only the most expensive |
| Solid Accessories for Reglistic Installation | - (| <u> </u> |

| Performance | Brava Old World Slate | Natural Slate |
|------------------------------------|--------------------------|--|
| Fire Retardant: Class A or Class C | \checkmark | \checkmark |
| Wind Resistance: 188+ mph* | \checkmark | * |
| Impact Resistance: Class 4 | \checkmark | Varies by product |
| Freeze/Thaw Resistant | \checkmark | May spall in alpine regions |
| Maintenance-Free | \checkmark | Requires inspection and repair throughout the life cycle |
| Colorfast | \checkmark | Only some varieties |
| Hail Warrantied | \checkmark | Varies by product |

| Installation | Brava Old World Slate | Natural Slate |
|----------------------------|--------------------------|--|
| Lightweight | \checkmark | * |
| Estimated Waste Factor | Low | High; slates with hairline cracks or broken during install will be discarded |
| Gun Nailed in Cold Weather | \checkmark | × |











*Brava tiles are tested and approved to withstand wind speeds of up to 188 mph with nails and up to 211 mph with high wind / screw installation.

Tolerances +or-1/2". All specifications subject to change without notice.

The printed colors shown may vary from actual colors. Before making a final selection, be sure to review actual material samples and roof installations. Please contact your salesperson for further assistance.

In order to achieve certain fire and wind ratings, special installation instructions may be required. Please reference Brava Roof Tile installation manuals at www.BravaRoofTile.com for more details.

bravarooftile.com • (844) 290-4196 • info@bravarooftile.com