

Technical Bulletin

Installation Supplement

May 19, 2023

Revised February 5, 2024



Wind Warranty Installation Requirements

Summary Brava tiles are tested and approved to withstand high-wind events and offer best-in-class warranty coverage. Brava's Limited Lifetime Warranty covers wind damage assessed to be due to a manufacturing defect up to 130 mph, depending on the fasteners used and installed exposure. Use the tables below to determine installation requirements and associated wind warranty eligibility.

Contents Verify you are using the correct table to choose installation specifications.
 Table 1 - **Brava Cedar Shake** and **Brava Slate** – Wind Warranty Matrix
 Table 2 - **Brava Barrel Tile** – Wind Warranty Matrix
















Table 1 - Brava Cedar Shake and Brava Slate – Wind Warranty Matrix				
<div>Brava Cedar Shake</div>  <div>Brava Slate</div> 		Fastener Requirements*	Maximum Exposure	Warranty Eligibility
	STANDARD	(2) 0.120" x ≥ 1 3/4" Ring Shank Roofing Nails 	≤ 10" 	90 MPH 
	ALTERNATE	(2) 0.120" x ≥ 1 3/4" Ring Shank Roofing Nails 	≤ 8" 	110 MPH 
	RECOMMENDED	(2) #8 x ≥ 2" Screws  High Wind Installation	≤ 10" 	130 mph 

Table 2 - Brava Barrel Tile – Wind Warranty Matrix				
Brava Spanish Barrel Tile		Fastener Requirements*	Maximum Exposure**	Warranty Eligibility
	STANDARD	(2) 0.120" x ≥ 2" Ring Shank Roofing Nails 	≤ 13" 	110 mph 
		Brava Mission Barrel Tile 	RECOMMENDED	(2) #8 x ≥ 2" Screws  High Wind Installation

Resources	<p>Brava provides installation guidance for all products at https://www.bravarooftile.com/resources/.</p> <p>Brava Technical Support offers Online and Remote Installation Training and Installation Support for all Brava products. Training prior to beginning installation can prevent costly delays. Please schedule training early to ensure availability.</p> <p>Access Online Training, View Resources, and Request Support through the Technical Support Portal at https://www.bravarooftile.com/technical-support.</p>
Warranty Registration	<p>Brava's Limited Lifetime Warranty can be viewed in full at bravarooftile.com.</p> <p>This bulletin is not intended to replace the full warranty and only addresses wind warranty installation requirements. Warranty eligibility requires meeting all published installation instructions. To register your warranty, go to https://www.bravarooftile.com/customer-service/warranty-registration/.</p>
Questions	<p>If you have any questions regarding Brava Roof Tile products and manufactured accessories, call 844-290-4196. Or contact us through the Technical Support Portal.</p>
Notes	<p>* Fasteners must be of sufficient length to penetrate 3/4" into the sheathing or completely through the sheathing. When a fastener gauge or length is specified, a longer or larger fastener may be acceptable depending on code, application, or availability. Brava requires two (2) fasteners per tile for all roofing products. Screw drive head type is not specified and may vary.</p> <p>** Prior to this publication, installation instructions for Brava Spanish Barrel Tile specified a 13.5" maximum exposure for all applications. Effective as of this publication, Brava recommends using 13" as the maximum Field Tile exposure for installations of Brava Spanish Barrel Tile. This change is to provide the best installation experience, product performance, and building code compliance across the nation. While code requirements, code enforcement officials, or desired warranty coverage may necessitate adherence to this new standard, there may be some applications where a prior standard may be authorized or approved.</p>